



# Eco-Tuff™ Non Skid Coating

ET-121014.v1

**DESCRIPTION:** The perfect balance of the highest quality 100% Acrylic emulsion and Urethane dispersion with advanced bio-based technology that offers outstanding abrasion, hot tire pick-up, chemical, water, and weather resistance for interior or exterior use. It is a breathable self sealing, uniquely hard yet resilient rubberized non-skid coating with a non-aggressive barefoot friendly texture. Eco-Tuff Non-Skid Coating may be topcoated with other Eco-Tuff coatings for color or sheen enhancements and may add our recycled glass powders. Use with Eco-Tuff Primers for your specific application.

Our industry changing bio-based chemistry makes high performance possible without toxic solvents or noxious lingering odors. Eco-Tuff not only meets the most stringent V.O.C. regulations, it is engineered with renewably sourced and recycled content, making it the most sustainable coating on the market today. Sustainability, performance and value are the cornerstones of the EcoProCote brand without compromise.



**INTENDED USE:** Properly profiled, clean and dry compatible surfaces: Concrete walkways, ramps, parking garage, stairwells, wood decks, wood docks, fiberglass boat decks, and most primed metals.

**SHEEN:** Satin **MESH OPTIONS:** Standard Mesh (Comparable to 36 Grit), Fine Mesh: (Comparable to 60 Grit)

**COLOR OPTIONS:** (12) Standard Pretinted or Color Pack Options in standard commercial grade or infrared reflective (I.R.) pigments. Custom colors available.

**PACKAGING:** 1 Gallon, 5 Gallon, 55 Gallon, 275 Gallon Tote

### The Smarter Way to Add Traction!

- Resilient Non-Abrasive • Excellent Flow & Adhesion
- Hard Wearing Chemistry • Work in Occupied Spaces
- Fast Return to Service • Most "LEED Potential"

### Solvent-Free Co-Polymers | NMP-Free | VOC-Free Glycol Ether Free | Virtually Odorless | Tough Barrier



85-120 Sq.Ft. Per  
Gallon Coverage



Fast 1 Hour Dry  
Time Typical



Surface Temp.  
45°F-95°F

(Avoid exterior application  
if rain is in the forecast  
within 24 hours.)



Soap and water  
clean-up.

#### TECHNICAL DATA:

- V.O.C. Regulatory = 0 g/L
- Bio-Based Content = 17%
- Recycled Content = 30%
- Flash Point = Non Flammable
- Freeze Point = 32°F / 0°C
- Hazardous Components = None
- Protection A: Safety Glasses

#### INGREDIENT DISCLOSURE:

INGREDIENTS:	CAS#:
Acrylic-Urethane Co-Polymer	N/A (Non-Haz)
Bio-Based Emulsion	N/A (Non-Haz)
Water	7732-18-5
Silica-Free Recycled Filler	N/A (Non-Haz)
Recycled Rubber Granules	N/A (Non-Haz)
Solvent Free Surfactants	N/A (Non-Haz)
Solvent Free Wax Emulsion	N/A (Non-Haz)

NOTE: Normal application poses no hazard to the release of respirable mineral filler, but grinding or sanding dried films of this product may yield respirable dust. In such case, use proper safety precautions.

Eco-Tuff™ Rubberized Non-Skid Coating	
HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	A

**POTENTIAL USGBC LEED POTENTIAL:** MR Credit 3- Materials Reuse, MR Credit 6- Recycled Content, MR Credit 5- Regional Materials, MR Credit 6- Rapidly Renewable Materials, IEQ Credit 4- Low Emitting materials, ID Credit 1- Innovation in Design.



Made in the U.S.A.



**Eco Safety Products**

Phoenix, Arizona U.S.A.  
Tel: (602)305-9397

www.ecosafetyproducts.com