



FLAT (MATTE)

Storage:

Protect from frost/freezing.

Where to use:

Use for interior walls and ceilings.

NOTE: For areas of very high humidity, e.g. bathrooms, ECOS Eggshell is recommended.

Preparation:

Surfaces should be sound, clean, dry and free from dust, dirt, grease, or surface contaminants. Prime bare plaster with ECOS Plaster Sealer, and bare sheetrock, with ECOS Wall Primer.

WARNING: Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm or purchase a Lead-Test Kit from your local retailer.

Application:

DO NOT THIN.

Stir gently and thoroughly before and during usage.

Applying two coats using a 3/8" or 1/2" shed resistant roller cover is generally best but the product can also be applied by 1800-2500 psi airless spray using a .015 or .017 tip. When brushing we recommend using a nylon, polyester, or synthetic blended brush.

Avoid temperatures below 41°F (5°C) and above 68°F (20°C). Temperatures outside margin may affect drying properties.

DRYING: With good ventilation - is touch dry within one hour and recoatable after two hours.

Clean hands and equipment with water.

Coverage:

Varies with porosity, but on hard non-porous surfaces, is typically 560 Sq Ft/Gallon (single coat).

Health & Safety:

Avoid contact with skin and eyes. Wash off splashes with water. Keep out of reach of children.