



## INTERIOR GLOSS and SEMI-GLOSS (Satin) Paint

---

### Storage:

Protect from frost/freezing.

### Where to use:

Interior woodwork and suitably primed or previously painted metal, etc.

### Preparation:

Ensure the surface is sound, dry and free of dust and grease.

For best results, clean with a Scotchbrite® or similar pad.

Remove dust with a tack cloth.

Paint will key to most finishes, but a test area is advisable.

WARNING: Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm.

### Preparation:

Bare wood - ensure the surface is smooth and dust free. Best results are achieved with one coat of ECOS Primer followed by one coat of ECOS Undercoat and two coats of ECOS Gloss/Satin Finish.

Bare Hardwoods - ask for advice.

Knots - treat with two liberal coats of ECOS White Knotting Compound.

Fillers - seal with ECOS Filler Sealer.

Bare iron and steel - prepare with ECOS Stainblock.

### Application:

NOTE: our gloss may be incompatible with other primers and undercoats.

IMPORTANT: Use only best quality soft paint brushes.

Work progressively along - do not over-brush, do not lay off, do not go back over painted areas.

Do not thin.

Stir gently and thoroughly before use.

Avoid applying below 41°F (5°C) or in direct sunlight.

Apply generously with a well loaded brush, shed resistant gloss roller, or may be applied by 1800-2500 psi airless spray using a .015 or .017 tip.

Allow to dry at least over night (and preferably 24 hours) between coats.

Normally touch dry in 1-2 hours.

Clean equipment with water.



## INTERIOR GLOSS and SEMI-GLOSS (Satin) Paint

---

### APPLICATION HINTS:

Paneled doors are best painted in sections e.g. panels, then rails, then stiles. Large flat areas (e.g. plain doors) are best painted with a gloss roller. Remove door furniture. Hardening continues for approx 7 to 10 days - avoid wetting and scuffing for this period.

### Coverage:

Varies with porosity, but on smooth, non porous surfaces:

110 Sq Ft per Quart (single coat)

440 Sq Ft per Gallon (single coat)

### Maintenance:

Clean with a damp cloth using dilute mild detergent. Do not use harsh, abrasive or alkaline cleaners. Do not allow pooling.

### Health & Safety:

Avoid contact with the skin and eyes. Wash off splashes with water. Keep out of the reach of children.