



PASSIVATING WHITE SATIN PAINT (Patent pending)

Storage:

Protect from frost/freezing.

Where to use:

Use on interior woodwork and previously painted metal, MDF, radiators, etc (not floors unless over-coated with floor paint). Apply 2 coats directly to the problem areas.

This is a White paint - If a colored finish is needed, either ECOS Gloss, Semi-Gloss or Feng Shui may be applied over the top of this.

Preparation:

Surfaces should be clean, dry and free from dust and grease.

The previously applied paint must be fully dry/cured and not oily.

For best results, clean with a Scotchbrite® (or similar) pad.

Will adhere to most surfaces but a test is advisable.

Application:

DO NOT THIN.

Stir gently and thoroughly before use.

Use best quality soft paint brushes.

Work progressively along, do not over-brush, lay off, or go back over painted areas.

Apply generously with a well loaded brush.

Best results are achieved with two coats.

Normally touch dry in 1-2 hrs.

Allow to dry at least over night between coats.

Avoid applying below 5 degrees C or in direct sunlight.

Clean equipment with water.



PASSIVATING WHITE SATIN PAINT (Patent pending)

APPLICATION HINTS

Paneled doors are best painted in sections e.g. panels, then rails, then stiles.

Large flat areas (e.g. plain doors) are best painted with a gloss roller. Remove door furniture.

Hardening continues for approx 7 - 10 days; avoid wetting & scuffing for this period.

Avoid temperatures below 41°F (5°C) and above 68°F (20°C).

Coverage:

Varies with porosity, but on hard non-porous surfaces is typically 110 Sq Ft per Quart or 440 Sq Ft per Gallon (single coat)

Maintenance:

Clean with a damp cloth using dilute mild detergent. Do not use harsh, abrasive or alkaline cleaners. Do not allow pooling.

Health & Safety:

Avoid contact with skin and eyes. Wash off splashes with water. Keep out of reach of children.