



ATMOSPHERE PURIFYING WALLPAINT (Patent pending)

Storage:

Protect from frost/freezing.

Where to use:

Interior walls and ceilings.

ECOS Atmosphere Purifying Paint gives a pleasant, wipeable matt finish and removes VOCs and Formaldehyde down to ~1 PPM.

Not ideal for areas subject to very frequent wetting.

Preparation:

Surfaces should be sound, clean, dry and free from dust, dirt, grease, or surface contaminants.

Prime bare plaster or plasterboard, with ECOS Plaster Sealer.

WARNING: Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm.

Application:

DO NOT THIN.

Stir gently and thoroughly before and during usage.

Applying two coats using a 3/8" or 1/2" shed resistant roller cover is generally best but may also be applied via 1800-2500 psi airless spray using a .015 or .017 tip.

When brushing we recommend using a nylon, polyester, or synthetic blended brush.

Always maintain a wet edge to minimize lapping.

Avoid temperatures below 41°F (5°C) and above 68°F (20°C).

DRYING: With good ventilation - is touch dry within one hour and recoatable after two hours.

Clean equipment with water.

Coverage:

Varies with porosity, but on hard non-porous surfaces:

520 Sq Ft per Gallon (single coat)

Health & Safety:

Avoid contact with skin and eyes. Wash off splashes with water. Keep out of reach of children.