



MASONRY PAINT (Smooth)

Storage:

Protect from frost/freezing.

Where to use:

For Exterior and Interior use on all masonry including stone, cement, render, brick, concrete, etc. Not suitable for Floors.

NOTE: This superior quality product has been specially formulated to inhibit mold and algal growth, but in keeping with our environmental credentials it contains no algaecide, so is not suitable for areas which are permanently wet.

Preparation:

Surfaces should be sound, clean, dry and free from dirt, loose and flaking material, and fungal/algal growth. Such growth must be removed and the cause removed prior to painting.

Loose material may be removed by a stiff brush. Soft or crumbly substrates should be pre-treated with ECOS Stabilizing Solution.

WARNING: Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm or purchase a Lead-Test Kit from your local retailer.

Application:

DO NOT THIN.

Stir gently and thoroughly before and during usage.

Applying two coats using a brush, or a 3/8" or 1/2" shed resistant roller cover is generally best but the product can also be applied via 1800-2500 psi airless spray. When brushing we recommend using a nylon, polyester, or synthetic blended brush.

Always maintain a wet edge to minimize lapping. Do not over-brush, dry-brush, or layoff.

Avoid going back over coated areas.

Best results are normally achieved with two coats.

Allow minimum of six hours between coats.

Avoid temperatures below 41°F (5°C) and above 68°F (20°C). Temperatures outside margin may affect drying properties.

DO NOT APPLY IF THERE IS A RISK OF RAIN OR FROST.

Drying Times:

Normally touch dry in 1 - 2 hours. The second coat may be applied after 4 - 6 hours.



MASONRY PAINT (Smooth)

Coverage:

Varies with porosity:
220-390 Sq Ft per Gallon (single coat)

Clean Up:

Clean hands and equipment with warm water.

Health & Safety:

Avoid contact with skin and eyes. Wash off splashes with water. Keep out of reach of children and avoid overexposure.