



VINYL SIDING AND SHUTTER PAINT

Storage:

Protect from frost/freezing.

Where to use:

For vinyl siding and shutters.

NOTE: Many vinyl siding/shutter manufacturers recommend that you do not paint them a darker color than original. Please check with your supplier/contractor to be sure yours is suitable. If in doubt, please contact us for advice.

Preparation:

Surfaces must be sound, clean, dry and free from dirt, loose and flaking material, and fungal/algal growth. Cleaning with water and very mild detergent is usually sufficient but, in case of more serious contamination, a power washer may be needed. Allow time for the siding to dry, allowing for water to drain from cracks and gaps.

Application:

DO NOT THIN.

Do not apply if there is a risk of rain or frost, preferably when air temperature is over 41°F (5°C). For best results, do not work on surfaces that are in direct sunlight.

Stir gently and thoroughly before use.

Apply by brush, roller or airless spray, working along each siding strip, starting at the top of the section. Work around the building to avoid working on areas in full sun.

Best results may require two coats, especially where you are introducing a great change in color. If a second coat is applied, allow a minimum of six hours between coats. Normally touch dry in 1-2 hours.

Clean equipment with water.

Coverage:

One Gallon will normally cover more than 500 Sq Ft per coat.

Health & Safety:

Avoid contact with skin and eyes. Wash off splashes with water. Keep out of reach of children.