

Application Notes

Pet Dwellings Paint

Where to use:

ECOS Pet Dwellings Paint can be used on all types of pet dwellings, including dog kennels, bird cages and terrariums.

Preparation:

Surfaces must be clean, dry, sound, and free from dirt, dust, grease and surface contaminants. Clean stubborn areas with mild detergent. Rinse and dry thoroughly before applying.

Coverage:

Spread rate depends upon the substrate porosity and finish type. Maximum spread rate is 140 sq. ft. per Quart.

Application:

DO NOT THIN.

Stir gently and thoroughly before and during usage.

Can be applied using a good quality synthetic brush; or rolled using a shed resistant 3/8" to 1/2" roller cover; or applied using an airless spray 0.015" – 0.017" tip at 1600-1800 PSI.

Best results achieved with two coats.

Avoid applying below 50°F (10°C).

Normally dries to the touch in one hour and can be recoated in two. Prior to recoating, ensure the first coat is fully dry before application.

Clean Up:

Clean hands and equipment with warm soapy water.

Storage:

Protect from frost/freezing.

Disposal:

Dispose of in accordance with local ordinance.

Health and safety:

Avoid contact with skin and eyes. Wash off splashes with water.

Keep out of reach of children.

Do not ingest.

