



MULTI-PURPOSE GYPSUM FILLER

Storage:

Protect from frost/freezing.

Where to use:

This is the ideal filler suitable for a variety of jobs, even large areas. Powder mixes easily to a smooth consistency, which dries to an easy to sand finish. Special binders give excellent adhesion. Use to fill holes, cover joints, etc.

Preparation:

Ensure crack or hole is dry and free from loose or dusty material.

Touch up any nails and screw heads with two-coats of ECOS Stainblock, to avoid rust-staining.

WARNING: Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm.

Application:

Mix 2 parts Filler with 1 part water (approx) to a smooth paste. The filler is ready for use in about one minute and remains workable for more than 20 minutes.

Press filler paste into hole with a filling knife/trowel. Fill the hole slightly proud.

Sand, when fully dry, to a smooth flat surface and brush/wipe free of dust. Special easy-sand formula!

Normally sets fully in around 1 to 2 hours.

Before painting, seal with one coat of ECOS Filler-Sealer and allow to dry fully.

Clean bowl and tools with warm water. Do not wash excess material into drains, but allow to dry on paper, then dispose of as household trash.

Health & Safety:

Avoid contact with skin and eyes. Wash off splashes with water. Keep out of reach of children.