

Storage:

Protect from frost/freezing.

Where to use:

Use for exterior woodwork - doors, window frames, joinery, etc.

Not suited to teak or similar oily woods, flooring, decking or exterior furniture.

Preparation:

Ensure the wood is clean, dry, dust-free and free of oil and wax. Round off any sharp edges with sandpaper.

Previously varnished wood: Varnish will key to most varnishes and finishes but a test area is advised. A light sanding of a previously varnished area is usually beneficial.

Remove all loose and flaking varnish with medium grade abrasive paper and feather in edges.

WARNING: Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm.

Application:

DO NOT THIN. Stir gently and thoroughly before use.

Use only best quality soft paint brushes.

Work progressively along the grain with a well loaded brush.

Do not over-brush, or layoff. Avoid going back over coated areas.

Best results are normally achieved with 3 coats.

Normally touch dry in 1-2 hours. Allow to dry overnight (and preferably 24 hours) between coats.

Do not use in direct sunlight or on hot surfaces. Avoid temperatures below 41°F (5°C) and above 68°F (20°C).

Clean equipment and brushes with water.

Coverage:

Varies with porosity but is typically 110 Sq Ft/Quart or 430 Sq Ft/Gallon (single coat).

Health & Safety:

Avoid contact with skin and eyes. Wash off splashes with water. Keep out of reach of children.