

ReMARKable Clear Water Base Dry-Erase Hardener A 1:2

Material Safety Data Sheet

Date of Preparation: 01/09/13

24 HOUR EMERGENCY ASSISTANCE	GENERAL MSDS ASSISTANCE
CHEMTREC: (800)-424-9300	360 Coatings 800-936-2159
HEALTH HAZARD→2 FLAMMABILITY→1 REACTIVITY→1 SPECIAL→0	5556 YAHLSTREET STE A NAPLES FLORIDA 34109 CHEMTREC – (800)424-9300

*For acute and chronic health effects refer to the discussion in Section III

SECTION I: NAME

PRODUCT NAME: ReMARKable Clear Dry-Erase Hardener A
CHEMICAL NAME: Hydrophilic Aliphatic Polyisocyanate based on Hexamethylene Diisocyanate
CHEMICAL FAMILY: Aliphatic Isocyanate
TYPE OF USE: Coatings

SECTION II: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS: Residual diisocyanate monomer content: <0.1%

<u>INGREDIENTS</u>	<u>CAS #</u>	<u>%</u>
Hexane, 1,6-Diisocyanate, Homopolymer	28182-81-2	>60%
Hydrophilic Aliphatic Polyisocyanate based on Hexamethylene Diisocyanate	666723-27-9	<10%
Hexamethylene-1,6-Diisocyanate	822-06-0	< .5%
Isopropanol	67-63-0	< 1%
Proprietary	N/A	5-30%

SECTION III: HAZARD IDENTIFICATION

WARNING! **Color:** Light yellow **Form:** Liquid **Odor:** Slight
Toxic gases/fumes may be given off during burning or thermal decomposition. Closed container may forcibly rupture under extreme heat or when contents have been contaminated with water. Use cold water spray to cool fire-exposed containers to minimize the risk of rupture. Causes respiratory tract irritation. May cause allergic respiratory reaction. Harmful if inhaled. Respiratory sensitizer. Lung damage and respiratory sensitization may be permanent. Causes skin irritation. May cause allergic skin reaction. Skin sensitizer. Causes eye irritation. May cause lung damage.

Potential Health Effects

Primary Routes of Entry: Skin Contact, Inhalation, Eye Contact

Medical Conditions Aggravated by: Skin Allergies, Eczema, Asthma, Respiratory, Exposure Disorders

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2
DATE OF PREPARATION: 01/09/13

HUMAN EFFECTS AND SYMPTOMS OF OVEREXPOSURE

Inhalation

Acute Inhalation

Diisocyanate or polyisocyanate vapors or mist at concentrations above the exposure limits or guidelines can irritate (burning sensation) the mucous membranes in the respiratory tract (nose, throat, lungs) with symptoms of runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing difficulty). Persons with a preexisting, nonspecific bronchial hyperreactivity can respond to concentrations below the exposure limits or guidelines with similar symptoms as well as asthma attack or asthma-like symptoms. Exposure well above the exposure limits or guidelines may lead to bronchitis, bronchial spasm and pulmonary edema (fluid in lungs). Chemical or hypersensitivity pneumonitis, with flu-like symptoms (e.g. fever, chills), has also been reported. These symptoms can be delayed up to several hours after exposure. These effects are usually reversible.

Isopropanol: May cause nervous system effects which can include symptoms of dizziness, incoordination, headache, numbness, and/or confusion

Chronic Inhalation

As a result of previous repeated overexposures or a single large dose, certain individuals may develop sensitization to diisocyanates or polyisocyanates (asthma or asthma-like symptoms) that may cause them to react to a later exposure to diisocyanates or polyisocyanates at levels well below the exposure limits or guidelines. These symptoms, which can include chest tightness, wheezing, cough, shortness of breath or asthmatic attack, could be delayed up to several hours after exposure. Extreme asthmatic reactions can be life threatening. Similar to many non-specific asthmatic responses, there are reports that once sensitized an individual can experience these symptoms upon exposure to dust, cold air, or other irritants. This increased lung sensitivity can persist for weeks and in severe cases for several years. Sensitization can be permanent. Chronic overexposure to diisocyanates has also been reported to cause lung damage (including fibrosis, decrease in lung function) that may be permanent.

Isopropanol: Chronic exposure to organic solvents has been associated with various neurotoxic effects including permanent brain and nervous system damage

Skin Contact

Acute Skin Contact

Causes irritation with symptoms of reddening, itching, and swelling. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Cured material is difficult to remove.

Isopropanol: Not expected to be irritating

Chronic Skin Contact

Prolonged contact can cause reddening, swelling, rash, and, in some cases, skin sensitization. Animal tests and other research indicate that skin contact with diisocyanates can play a role in causing isocyanate sensitization and respiratory reaction. This data reinforces the need to prevent direct skin contact with isocyanates.

Isopropanol: Chronic exposure may cause symptoms similar to those described in chronic inhalation.

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2

DATE OF PREPARATION: 01/09/13

Eye

Acute Eye Contact

Causes irritation with symptoms of reddening, tearing, stinging, and swelling. May cause temporary corneal injury. Vapor may cause irritation with symptoms of burning and tearing.

Isopropanol: May cause irritation with symptoms of reddening, tearing, and stinging

Chronic Eye Contact

Prolonged vapor contact may cause conjunctivitis.

Ingestion

Acute Ingestion

May cause irritation; Symptoms may include abdominal pain, nausea, vomiting, and diarrhea.

Isopropanol: Symptoms of ingestion may include abdominal pain, nausea, vomiting, and diarrhea. May cause nervous system effects, which can include symptoms of dizziness, incoordination, headache, numbness, and/or confusion.

Carcinogenicity

Isopropanol: IARC – Overall evaluation: 3 Not classifiable as to carcinogenicity to humans.

IARC – Overall evaluation: 1 Carcinogenic to humans

IV. FIRST AID MEASURES

Eye Contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Use lukewarm water if possible. Use fingers to ensure that eyelids are separated and that the eye is being irrigated. Then remove contact lenses, if easily removable, and continue eye irrigation for not less than 15 minutes. Get medical attention if irritation develops.

Skin Contact

Immediately remove contaminated clothing and shoes. Wash off with soap and water. Use lukewarm water if possible. Wash contaminated clothing before reuse. For severe exposures, immediately get under safety shower and begin rinsing. Get medical attention if irritation develops and persists.

Inhalation

Move to an area free from further exposure. Get medical attention immediately. Administer oxygen or artificial respiration as needed. Asthmatic symptoms may develop and may be immediate or delayed up to several hours. Extreme asthmatic reactions can be life threatening.

Ingestion

Do not induce vomiting. Wash mouth out with water. Do not give anything by mouth to an unconscious person. Get medical attention.

Notes to physician

Eyes: Stain for evidence of corneal injury. If cornea is burned, instill antibiotic/steroid preparation as needed. Workplace vapors could produce reversible corneal epithelial edema impairing vision. Skin: This compound is a skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burn. Ingestion: Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of the compound. Inhalation: Treatment is essentially symptomatic.

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2
DATE OF PREPARATION: 01/09/13

An individual having a dermal or pulmonary sensitization reaction to this material should be removed from further exposure to any diisocyanate.

SECTION V: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Dry chemical, carbon dioxide (CO₂), foam, water spray for large fires.

Special Fire Fighting Procedures

Firefighters should wear NFPA compliant structural firefighting protective equipment, including self-contained breathing apparatus and NFPA compliant helmet, hood, boots and gloves. Avoid contact with product. Decontaminate equipment and protective clothing prior to reuse. During a fire, isocyanate vapors and other irritating, highly toxic gases may be generated by thermal decomposition or combustion. Exposure to heated diisocyanate can be extremely dangerous.

Unusual Fire/Explosion Hazards

Closed container may forcibly rupture under extreme heat or when contents are contaminated with water (CO₂ formed). Use cold-water spray to cool fire-exposed containers to minimize the risk of rupture. Large fires can be extinguished with large volumes of water applied from a safe distance, since reaction between water and hot diisocyanate can be vigorous.

SECTION VI: ACCIDENTAL RELEASE MEASURES

Spill and Leak Procedures

Evacuate non-emergency personnel. Isolate the area and prevent access. Remove ignition sources. Notify management. Put on protective equipment. Control source of the leak. Ventilate. Contain the spill to prevent spread into drains, sewers, water supplies, or soil. Call Bayer at 412-923-1800 for assistance and advice. Major Spill or Leak (Standing liquid): To minimize vapor, cover the spillage with fire fighting foam (AFFF). Released material may be pumped into closed, but not sealed, metal container for disposal. Process can generate heat. Minor Spill or Leak (Wet surface): Cover spill area with suitable absorbent material (Kitty Litter, Oil-Dri®, etc). Saturate absorbent material with neutralization solution and mix. Wait 15 minutes. Collect material in open-head metal containers. Repeat applications of decontamination solution, with scrubbing, followed by absorbent until the surface is decontaminated. Check for residual surface contamination. Swype® test kits have been used for this purpose. Apply lid loosely and allow containers to vent for 72 hours to let carbon dioxide (CO₂) escape.

Additional Spill Procedures/Neutralization

Neutralization solutions:

- (1) Colorimetric Laboratories Inc. (CLI) decontamination solution.
- (2) A mixture of 75% water, 20 non-ionic surfactant (e.g. Poly-Tergent SL-62, Tergitol TMN-10) and 5 n-propanol.
- (3) A mixture of 80% water, 20 non-ionic surfactant (e.g. Poly-Tergent SL-62, Tergitol TMN-10).
- (4) A mixture of 90% water, 3-8 ammonium hydroxide or concentrated ammonia, and 2 liquid detergent.

CHEMTREC should be immediately notified (800-424-9300) when this product is unintentionally released from its container during its course of distribution, regardless of the amount released. Distribution includes transportation, storage incidental to transportation, loading and unloading. Such notification must be immediate and made by the person having knowledge of the release.

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2
DATE OF PREPARATION: 01/09/13

SECTION VII: HANDLING AND STORAGE

Storage Temperature:

Minimum: 7°C
Maximum: 25°C

Storage Period

Unopened for 6 Months @ 25 °C (77 °F): after receipt of material by customer

Handling/Storage Precautions

Do not breathe vapors, mists, or dusts. Use adequate ventilation to keep airborne isocyanate levels below the exposure limits. Wear respiratory protection if material is heated, sprayed, used in a confined space, or if the exposure limit is exceeded. Warning properties (irritation of the eyes, nose and throat or odor) are not adequate to prevent overexposure from inhalation. This material can produce asthmatic sensitization upon either single inhalation exposure to a relatively high concentration or upon repeated inhalation exposures to lower concentrations. Individuals with lung or breathing problems or prior allergic reactions to isocyanates must not be exposed to vapor or spray mist. Avoid contact with skin and eyes. Wear appropriate eye and skin protection. Wash thoroughly after handling. Do not breathe smoke and gases created by overheating or burning this material. Decomposition products can be highly toxic and irritating. Store in tightly closed containers to prevent moisture contamination. Do not reseat if contamination is suspected.

Further Info on Storage Conditions

Employee education and training in the safe use and handling of this product are required under the OSHA Hazard Communication Standard 29 CFR 1910.1200.

SECTION VIII: EXPOSURE CONTROLS/PERSONAL PROTECTION

Homopolymer of Hexamethylene Diisocyanate (28182-81-2)

Exposure Limit

Time Weighted Average (TWA): 0.5 mg/m³

Exposure Limit

Short Term Exposure Limit (STEL): 1.00 mg/m³ (15-min)

Hexamethylene-1,6-Diisocyanate (822-06-0)

US. ACGIH Threshold Limit Values

Time Weighted Average (TWA): 0.005 ppm

Exposure Limit

Ceiling Limit Value: 0.02 ppm

Isopropanol (67-63-0)

US. ACGIH Threshold Limit Values

Time Weighted Average (TWA): 200 ppm

US. ACGIH Threshold Limit Values

Short Term Exposure Limit (STEL): 400 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

PEL: 400 ppm, 980 mg/m³

US. ACGIF Threshold Limit Values

Hazard Designation: Group A4 Not classifiable as a human carcinogen

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2
DATE OF PREPARATION: 01/09/13

Industrial Hygiene/Ventilation Measures

Good industrial hygiene practice dictates that worker protection should be achieved through engineering controls, such as ventilation, whenever feasible. When such controls are not feasible to achieve full protection, the use of respirators and other personal protective equipment is mandated. Exhaust air may need to be cleaned by scrubbers or filters to reduce environmental contamination. Curing ovens must be ventilated to prevent emissions into the workplace. If oven off-gases are not vented properly (i.e. they are released into the work area), it is possible to be exposed to airborne monomeric HDI.

Respiratory Protection

A respirator that is recommended or approved for use in isocyanate-containing environments (air-purifying or fresh air-supplied) may be necessary for spray applications or other situations such as high temperature use which may produce inhalation exposures. A supplied-air respirator (either positive pressure or continuous flow-type) is recommended. Before an air-purifying respirator can be used, air monitoring must be performed to measure airborne concentrations of HDI monomer and HDI polyisocyanate. Specific conditions under which air-purifying respirators can be used are outlined in the following sections. Observe OSHA regulations for respirator use (29 CFR 1910.134).

SPRAY APPLICATION:

Good industrial hygiene practice dictates that when isocyanate-based coatings are spray applied, some form of respiratory protection should be worn. During the spray application of coatings containing this product the use of a supplied-air (either positive pressure or continuous flow-type) respirator is mandatory when ONE OR MORE of the following conditions exists:

- the airborne isocyanate concentrations are not known; or -the airborne isocyanate monomer concentrations exceed 0.05 ppm averaged over eight (8) hours (10 times the 8 hour TWA exposure limit); or
- the airborne polyisocyanate (polymeric, oligomeric) concentrations exceed 5 mg/m³ averaged over 8 hours or 10 mg/m³ averaged over 15 minutes (10 times the 8 hour TWA or the 15 minute STEL exposure limits); or
- operations are performed in a confined space (See OSHA Confined Space Standard, 29 CFR 1910.146).

A properly fitted air-purifying (combination organic vapor and particulate) respirator, proven by test to be effective in isocyanate-containing spray paint environments, and used in accordance with all recommendations made by the manufacturer, can be used when ALL of the following conditions are met:

- the airborne isocyanate monomer concentrations are known to be below 0.05 ppm averaged over eight (8) hours (10 times 8 hour TWA exposure limit); and
- the airborne polyisocyanate (polymeric, oligomeric) concentrations are known to be below 5 mg/m³ averaged over 8 hours or 10 mg/m³ averaged over 15 minutes (10 times the 8 hour TWA or the 15 minute STEL exposure limits); and
- a NIOSH-certified End of Service Life Indicator or a change schedule based upon objective information or data is used to ensure that cartridges are replaced before the end of their service life.

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2
DATE OF PREPARATION: 01/09/13

In addition, prefilters should be changed whenever breathing resistance increases due to particulate buildup.

NON-SPRAY OPERATIONS:

During non-spray operations such as mixing, batch-making, brush or roller application, etc., at elevated temperatures (for example, heating of material or application to a hot substrate), it is possible to be exposed to airborne isocyanate vapors. Therefore, when the coatings system will be applied in a non-spray manner, a supplied-air (either positive pressure or continuous flow-type) respirator is mandatory when ONE OR MORE of the following conditions exists:

- the airborne isocyanate concentrations are not known; or the the airborne isocyanate monomer concentrations exceed 0.05 ppm averaged over eight (8) hours (10 times the 8 hour TWA exposure limit); or
- the airborne polyisocyanate (polymeric, oligomeric) concentrations exceed 5 mg/m³ averaged over 8 hours or 10 mg/m³ averaged over 15 minutes (10 times the 8 hour TWA or the 15 minute STEL exposure limits); or
- operations are performed in a confined space (See OSHA Confined Space Standard, 29 CFR 1910.146).

A properly fitted air-purifying (combination organic vapor and particulate) respirator, proven by test to be effective in isocyanate-containing paint environments, and used in accordance with all recommendations made by the manufacturer, can be used when ALL of the following conditions are met:

- the airborne isocyanate monomer concentrations are known to be below 0.05 ppm averaged over eight (8) hours (10 times 8 hour TWA exposure limit); and
- the airborne polyisocyanate (polymeric, oligomeric) concentrations are known to be below 5 mg/m³ averaged over 8 hours or 10 mg/m³ averaged over 15 minutes (10 times the 8 hour TWA or the 15 minute STEL exposure limits); and
- a NIOSH-certified End of Service Life Indicator or a change schedule based upon objective information or data is used to ensure that cartridges are replaced before the end of their service life. In addition, prefilters should be changed whenever breathing resistance increases due to particulate buildup.

Hand Protection

Gloves should be worn. Nitrile rubber gloves, Butyl rubber gloves, Neoprene gloves.

Eye Protection

When directly handling liquid product, eye protection is required. Examples of eye protection include a chemical safety goggle, or chemical safety goggle in combination with a full face shield when there is a greater risk of splash.

Skin and body protection

Avoid all skin contact. Depending on the conditions of use, cover as much of the exposed skin area as possible with appropriate clothing to prevent skin contact. Gloves, long sleeved shirts and pants.

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2
DATE OF PREPARATION: 01/09/13

Medical Surveillance

All applicants who are assigned to an isocyanate work area should undergo a pre-placement medical evaluation. A history of eczema or respiratory allergies such as hay fever, are possible reasons for medical exclusion from isocyanate areas. Applicants who have a history of adult asthma should be restricted from work with isocyanates. Applicants with a history of prior isocyanate sensitization should be excluded from further work with isocyanates. A comprehensive annual medical surveillance program should be instituted for all employees who are potentially exposed to diisocyanates. Once a worker has been diagnosed as sensitized to any isocyanate, no further exposure can be permitted.

Additional Protective Measures

Emergency showers and eye wash stations should be available. Educate and train employees in the safe use and handling of this product. Follow all label instructions.

SECTION IX: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Color:	Light yellow
Odor:	Slight
Freezing Point:	No Data Available
Boiling Point/Range:	Decomposition, Estimated based on component(s)
Flash Point:	185 °C (365 °F)
Lower Explosion Limit:	Not Established
Upper Explosion Limit:	Not Established
Vapor Pressure:	HDI Polyisocyanate: 5.2 X 10⁻⁹ @ 68 F (20 C) mmHg
Specific Gravity:	Approximately 1.15 @ 20 °C (68 °F)
Solubility in Water:	Insoluble - Reacts slowly with water to liberate CO₂ gas
Autoignition Temperature:	Approximately 445 °C (833 °F)
Decomposition Temperature:	Approximately 181 °C (357 °F)
Viscosity, Dynamic:	Approximately 800 mPa.s @ 20 °C (68 °F)
Bulk Density:	Approximately 9.6 lb/gal
Molecular Weight:	500 Approximate Value, For the polyisocyanate
VOC	<50 Grams per liter

SECTION X: STABILITY AND REACTIVITY

Hazardous Reactions

Contact with moisture, other materials that react with isocyanates, or temperatures above 350 F (177 C), may cause polymerization.

Stability

Stable under normal conditions of use and storage.

Materials to avoid

Water, Amines, Strong Bases, Alcohols, Copper Alloys

Conditions to avoid

Heat, flames, and sparks. Protect from freezing.

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2
DATE OF PREPARATION: 01/09/13

Hazardous decomposition products

By Fire and High Heat: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke. Hydrogen cyanide, Isocyanate, Isocyanic Acid, Other undetermined compounds

SECTION XI: TOXICOLOGICAL INFORMATION

Toxicity Data for Homopolymer of Hexamethylene-1,6-Diisocyanate

Acute Oral Toxicity

LD50: > 5,000 mg/kg (Rat)

Estimated Value

Acute Inhalation Toxicity

LC50: 390-453 mg/m³, aerosol, 4 hrs (Rat, Male/Female)

RD50: 20.8 mg/m³, 3 hrs

Acute Dermal Toxicity

LD50: > 5,000 mg/kg (Rabbit)

Skin Irritation

(Rabbit, Draize)

Slightly irritating

Eye Irritation

(Rabbit, Draize)

Slightly irritating

Sensitization

Dermal: sensitizer (Guinea Pig, Maximization Test (GPMT))

Dermal: non-sensitizer (Guinea Pig, Buehler)

Inhalation: non-sensitizer (Guinea Pig)

Repeated Dose Toxicity

3 wks, inhalation: NOAEL: 3.7 - 4.3 mg/m³, (Rat)

90 days, inhalation: NOAEL: 3.3 - 3.4 mg/m³, (Rat)

Irritation to lungs and nasal cavity

Mutagenicity

Genetic Toxicity in Vitro: Ames: negative (Salmonella typhimurium. Metabolic Activation: with/without)

HGPRT Assay: Negative (Chinese Hamster ovary (CHO) cells, metabolic activation: with/without)

Genetic Toxicity in Vivo:

Micronucleus Assay: Negative (Mouse)

Negative

Carcinogenicity

Rat, male/female, inhalation, 2 yrs, 6 hrs/day, 5 days/week, Did not show carcinogenic effects in animal experiments

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2

DATE OF PREPARATION: 01/09/13

Toxicity to Reproduction/Fertility

One generation study, inhalation, daily, (rat male/female) NOAEL (parental): <0.3 ppm, NOAEL (F2): 0.3 PPM No effects on Reproductive parameters observed at doses tested

Developmental Toxicity/teratogenicity

Rat, female, inhalation, gestation days 0- 19, daily, NOAEL (teratogenicity): >0.3 ppm, NOAEL (maternal): < 0.3 ppm

No Teratogenic effects observed at doses tested, no fetotoxicity observed at doses tested

Neurological Effects

Rats exposed by inhalation, 6 hours/day, for approximately 3 weeks, to concentrations as high as 0.3 ppm showed no neurobehavioral effects or damage to nerve tissues

Toxicity Data for Isopropanol

Acute Oral Toxicity

LD50: 4,396 - 5,500 mg/kg (Rat)

Acute Inhalation Toxicity

LC50: 72.6 mg/l, 4 h (Rat)

Acute Dermal Toxicity

LD50: 12,800 mg/kg (Rat)

Eye irritation

(Rabbit, Draize)

Moderately Irritating

Sensitisation

Dermal: non-sensitizer (Guinea Pig, Buehler)

Repeated dose toxicity

90 Days, inhalation: NOAEL: 1500 ppm, (Rat)

Mutagenicity

Genetic Toxicity in Vitro:

Ames: Negative (Salmonella typhimurium, Metabolic Activation: with/without)

Genetic Toxicity in Vivo:

Micronucleus Assay: Negative (Mouse)

Negative

Toxicity to Reproduction/Fertility

Two generation study, oral, daily, (Rat)

NOAEL (F1): 500 mg/kg, NOAEL (F2): 500 mg/kg

Developmental Toxicity/teratogenicity

(Rat) inhalation, daily, NOAEL (teratogenicity): 8,575 mg/kg

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2
DATE OF PREPARATION: 01/09/13

SECTION XII: ECOLOGICAL INFORMATION

Ecological Data for Homopolymer of Hexamethylene Diisocyanate

Biodegradation

0, Exposure time: 28 Days, Not readily biodegradable.

Acute and Prolonged Toxicity to Fish

LCO: > 100 mg/l (Zebra fish (Brachydanio rerio), 96 hrs)

Acute Toxicity to Aquatic Invertebrates

ECO: > 100 mg/l (Water flea (Daphnia magna), 48 hrs)

Toxicity to Aquatic Plants

EC50: > 1,000 mg/l, (Green algae (Scenedesmus subspicatus), 72 hrs)

Toxicity to Microorganisms

EC50: > 1,000 mg/l, (Activated sludge microorganisms, 3 hrs)

Biodegradation

1 %, Exposure time: 28 d, i.e. not readily degradable

Acute and Prolonged Toxicity to Fish

LCO: > 100 mg/l (Zebra fish (Brachydanio rerio), 96 h)

Acute Toxicity to Aquatic Invertebrates

ECO: > 100 mg/l (Water flea (Daphnia magna), 48 h)

Toxicity to Aquatic Plants

EL50: 50- 100 mg/l, (Green algae (Scenedesmus subspicatus), 72 h)

Toxicity to Microorganisms

EC50: 5,560 mg/l, (Activated sludge microorganisms)

Ecological Data for Hydrophilic Aliphatic Polyisocyanate based on Hexamethylene Diisocyanate

Biodegradation

0 %, i.e. not readily degradable

Ecotoxicological reports on a comparable product

Acute and Prolonged Toxicity to Fish

LC50: 35.2 mg/l (Danio rerio (zebra fish), 96 h)

Ecotoxicological reports on a comparable product

Acute Toxicity to Aquatic Invertebrates

EC50: > 100 mg/l (Daphnia magna (Water flea), 48 h)

Ecotoxicological reports on a comparable product

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2
DATE OF PREPARATION: 01/09/13

Toxicity to Aquatic Plants

EC50: 72 mg/l, (Desmodesmus subspicatus (Green algae), 72 h)
Ecotoxicological reports on a comparable product

Toxicity to Microorganisms

EC50: > 10,000 mg/l, (activated sludge)
Ecotoxicological reports on a comparable product

Ecological Data for Heumethylene-1,6-Diisocyanate

Biodegradation

Aerobic, 42 %, Exposure time: 28 Days, Not readily biodegradable.

Acute and Prolonged Toxicity to Fish

LCO: > 82.8 mg/l (Zebra fish (Brachydanio rerio), 96 h)

Acute Toxicity to Aquatic Invertebrates

ECO: > 89.1 mg/l (Water flea (Daphnia magna), 48 h)

Toxicity to Aquatic Plants

EC50: > 77.4 mg/l, (Green algae (Scenedesmus subspicatus), 72 h)

Toxicity to Microorganisms

EC50: 842 mg/l, (Activated sludge microorganisms)

Ecological Data for Isopropanol

Biodegradation

95 %, Exposure time: 21 d, i.e. readily biodegradable

Acute and Prolonged Toxicity to Fish

11,830 mg/l (Fathead minnow (Pimephales promelas), 1 h)
11,160 mg/l (Fathead minnow (Pimephales promelas), 24 h)

Acute Toxicity to Aquatic Invertebrates

EC50: > 100 mg/l (Daphnia magna (Water flea), 48 h)

Toxicity to Aquatic Plants

EC50: > 1,000 mg/l, (scenedesmus subspicatus, 72 h)

Toxicity to Microorganisms

EC50: > 1,000 mg/l, (activated sludge, 3 h)

SECTION XIII: DISPOSAL CONSIDERATIONS

Waste Disposal Method

Waste disposal should be in accordance with existing federal, state and local environmental control laws.
Incineration is the preferred method.

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2
DATE OF PREPARATION: 01/09/13

Empty Container Precautions

Empty containers retain product residue; observe all precautions for product. Do not heat or cut empty container with electric or gas torch because highly toxic vapors and gases are formed. Do not reuse without thorough commercial cleaning and reconditioning. If container is to be disposed, ensure all product residues are removed prior to disposal.

SECTION XIV: TRANSPORT INFORMATION

Land Transport (DOT)

Proper Shipping Name: Other regulated substances, liquid, n.o.s. (contains Hexamethylene-1,6-Diisocyanate)
Hazard Class or Division: 9
UN/NA Number: NA3082
Packaging Group: III
Hazard Label(s): Class 9

Reportable Quantity: 45,359 kg (99,999 lb)

Sea transport (IMDG)

Non-Regulated

Air transport (ICAO/IATA) Non-Regulated

Additional Transportation Information

When in individual containers of less than the Product RQ, this material ships as non-regulated.

SECTION XV: REGULATORY INFORMATION

United States Federal Regulations

OSHA Hazcom Standard Rating: Hazardous

US. Toxic Substances Control Act: Listed on the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302):

Components:
None

SARA Section 311/312 Hazard Categories:

Acute Health Hazard, Chronic Health Hazard, Reactivity Hazard

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title HI Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A):

Components:
None

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title HI Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required:

Components:
None

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2
DATE OF PREPARATION: 01/09/13

US. EPA Resource Conservation and Recovery Act (RCRA) Composite List of Hazardous Wastes and Appendix VIII Hazardous Constituents (40 CFR 261):

If discarded in its purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. (40 CFR 261.20-24)

State Right-To-Know Information

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists:

<u>Weight</u>	<u>Components</u>	<u>CAS-No.</u>
60-100	Homopolymer of Hexamethylene Diisocyanate	28182-81-2
10-20	Homopolymer of Hexamethylene Diisocyanate	28182-81-2
1 - 5	Hydrophilic Aliphatic Polyisocyanate based on Hexamethylene Diisocyanate	666723-27-9

New Jersey Environmental Hazardous Substances List and/or New Jersey RTK Special Hazardous Substances Lists:

<u>Weight</u>	<u>Components</u>	<u>CAS-No.</u>
.1 – 1%	Hexamethylene-1,6-Diisocyanate	822-06-0
.1 – 1%	Isopropanol	67-63-0

California Prop. 65:

Warning! This product contains chemical(s) known to the State of California to be – Developmental toxin

<u>Weight</u>	<u>Components</u>	<u>CAS-No.</u>
<0.1	Methanol	67-56-1

SECTION XVI: OTHER INFORMATION

NFPA 704M Rating

Health 2
 Flammability 1
 Reactivity 1

Other

0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

HMIS Rating

Health 2*
 Flammability 1
 Physical Hazard 1

0=Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

ReMARKable CLEAR WB DRY ERASE HARDENER A 1:2
DATE OF PREPARATION: 01/09/13

* = Chronic Health Hazard

Disclaimer of Responsibility: This document is generated for the purpose of distributing health, safety, and environmental data. It is not a specification sheet nor should any displayed data be construed as a specification. The information on this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of this product. If the product is used as a component in another product, this MSDS information may not be applicable.